



# BOHEMI CHEMICALS

## Fiche Technique / Technical Data Sheet

### **POLYGLAS D4450**

#### **DESCRIPTION**

Waxes and copolymers emulsion.

#### **CHARACTERISTICS**

Parameters	test method	Specifications
Appearance	QCR017	Off white liquid
Solid content	QCR001-05	20 – 22

- pH (2001) at 20°C : 6 – 8
- Viscosity (0201) : 25 – 40 seconds

#### **PROPERTIES**

- gives a good wet and dry scratch resistance.
- provides an excellent surface protection during transportation and conveyance.
- ensures optimum slippery surface.

#### **APPLICATION**

- Dilution rate 1 to 3 % with demineralized water.
- Glass containers temperature 110-130°C.
- Application by spray system.
- Our Technical Service is ready to supply all the relevant information regarding the correct use of our products.

#### **STORAGE CONDITIONS**

- 12 months in original packing.
- Storage temperature 5 – 30°C
- Polyglas D4450 must be protected from frost during transport and storage

#### **SAFETY INFORMATION**

Material Safety Data Sheets (MSDS) are available for all products. These sheets contain important information that you may need to protect your employees and customers against any known health and safety hazards associated with our products. We recommend that you obtain copies of our MSDS before using our products in your facilities. We also suggest that you contact your suppliers of other materials recommended for use with our products for appropriate health and safety precautions before using them.